

MILLIKEN®

a MUELLER brand

1/2" - 2" MILLCENTRIC®

Eccentric Plug Valve



MUELLER

OVERVIEW OF VALVE DETAILS - 1/2" - 2"

The Milliken® criteria of quality, reliability, safety and value are embodied in the Millcentric® Eccentric valve, setting higher standards for dependable performance with excellent features achieved by the utilization of the very latest design and manufacturing techniques.

- Computer Aided Design
- High Integrity Casting
- CNC manufacturing delivers consistent sizes on all components

All complemented by a rigorous Quality Control System

BODY

The Millcentric® valve body casting is ASTM A536 65-45-12 ductile iron using high pressure molding techniques. Threaded connection available on 1/2" - 2" sizes. Flanged connection available on 2" size.

Flange diameter, thickness and drilling conform to ANSI B16.1 Class 125.

SEAT

The valve seat shall be furnished with an overlay of corrosion and abrasion resistant epoxy.

STEM SEAL

High integrity sealing by combining the advantages of a resilient and abrasion resistant U-Cup seal. From vacuum to high pressure, the self-adjusting sealing system (per AWWA C504) gives positive, trouble-free service and is retained independently of the plug stem or external torque device, thereby eliminating periodic maintenance.

BEARINGS

The plug rotates in permanently lubricated stainless steel bearings, located in the body and bonnet, along with upper and lower PTFE thrust washers which ensure consistently low operating torque.

PLUG

Supported on integral trunnions, the plug is totally encapsulated with an elastomer that is molded to the casting providing tight shut off even under vacuum conditions. High integrity corrosion-free sealing is achieved by a variety of abrasion resistant elastomers which protect the plug right up to the trunnions. When assembled, the light compression of the elastomers onto PTFE thrust washers prevents entry of abrasive materials into the bearings.

BONNET SEAL

Superior "O" ring sealing with metal / metal contact means lower bolting stresses compared with compression gaskets.

FLOW


The full round port design with streamlined internal contours gives the highest industry capacity straight through flow in the full open position, reducing turbulence and pressure drop and the effect of erosive media. Handling of sludges and slurries is therefore enhanced.

TRAVEL STOPS


Adjustable open and closed travel stops are fitted as standard on both wrench and gear operated Millcentric® valves.

1/2" - 2" MILLCENTRIC®

Eccentric Plug Valve



- Valve in closed position for bubble tight shut-off
- Normal flow direction gives pressure assisted sealing
- Torques are low even in reverse flow



- Plug rotates away from the seat for instant opening
- Seat wear and operating torque reduced
- No further seat contact until valve is closed again



- Design of Millcentric® plug valve allows modulating control over the full 90° travel
- Ideally suited for balancing service
- Standard rotary valve provides control and tight shut off in one valve



- Plug is out of flow path when fully open
- Straight through, uninterrupted smooth flow
- Round port reduces turbulence and erosion, lowers pumping costs and can be "pigged" to clean the pipeline

INSTALLATION

The Millcentric® plug valve is suitable for flow and shut-off in either direction. Seat end downstream is the preferred orientation and any reverse flow requirement should be stated at the time of order. For use on fluids with suspended solids, installation with the seat upstream and the valve stem horizontal is recommended with plug rotation to the top of the valve.

IN-LINE MAINTENANCE


In the unlikely event of stem leakage, the stem seals can be easily replaced without removing the bonnet. Access to the body for cleaning or inspection does not require removal from the line.

MODULAR CONSTRUCTION

Design of the bonnet and stem allows for on-site adaption of gear operators, power actuators, or extension devices on to standard valves. Conversion can be easily undertaken without removing the valve bonnet, thereby minimizing downtime.

POWER OPERATION


Pneumatic, electric or hydraulic operation is available, complete with accessories such as limit switches, solenoid valves and positioners when required.



1/2" - 2" MILLCENTRIC®

Eccentric Plug Valve

STANDARD MATERIALS OF CONSTRUCTION, FIG. 613A/611A, 1/2" - 2"



ITEM	COMPONENT	MATERIAL	QTY
1	Body	Ductile Iron ASTM A536	1
2	Plug	Rubber Coated Ductile Iron ASTM A536	1
3	Cap	Ductile Iron ASTM A536	1
4	Torque Collar Assembly	Ductile Iron ASTM A536	1
5	Journal Bearing	Stainless Steel	2
6	PTFE Washer (Grit Seal)	PTFE	2
7	O Ring	Elas. as Spec.	1
8	U Cup Seal	Elas. as Spec.	2
9	Seal Retaining Ring	Brass — ASTM B-138-675	1
10	Internal Snap Ring	Spring Steel	1
11	Cap Bolt	Steel (Zinc Plated)	AR
12	Close Stop	Steel (Zinc Plated)	1

TECHNICAL DATA

ORDERING INFORMATION

VALVE TYPES	DESIGNATION
Mechanical Joint Cast Iron	600
Mechanical Joint Ductile Iron	620
ANSI 125 Flanged Cast Iron Flat Face	601
ANSI 125 Flanged Ductile Iron Flat Face	611
ANSI 150 Flanged Ductile Iron Raised Face	621
ANSI 250 Flanged Ductile Iron Raised Face	602
ANSI 125 Grooved for Steel Pipe	606S
ANSI 125 Grooved for Ductile Pipe	606D
ANSI 150 Flanged 316SS	601S
SEAT	
Nickel (3" & Larger)	N
Epoxy (2-1/2" ONLY)	E
316SS (On Stainless Steel Valve ONLY)	S
Rubberlined	RL
Glasslined	GL
ELASTOMER TRIM	
EPDM	0
Buna-Nitrile	1
Viton	2
Neoprene	3
Natural	4
MANUAL OPERATORS	
Above Ground Gear and Handwheel	AGHW
Above Ground Gear with 2" Nut	AGNUT
Buried Gear with 2" Nut	BG
Memory Stop Gear with Handwheel	MGHW
Lever / Wrench (8" & smaller)	L
Direct Nut (8" & smaller)	TC

Example: 4" 601N3AGHW = 4" ANSI 125 Flanged, Nickel Seat, Neoprene plug with Above Ground Gear and Handwheel.

Valves are only tested for bi-directional shut-off if specified at time of order. Contact factory for bi-directional ratings.

Note: We recommend mechanical joint or buried flanged valves to have gear operators.

Note: We recommend valves for bi-directional service to have gear operators.

Note: Gear operators must be used on valve sizes up to 10" for bi-directional service.

PRESSURE RATING

12" and Smaller	ANSI 125	175 psi
14" and Larger	ANSI 125	150 psi
14" and Larger	ANSI 150	235 psi
20" and Smaller	ANSI 150	285 psi
12" and Smaller	ANSI 250	400 psi
14" and Larger	ANSI 250	300 psi

Body Hydrotest = 150% of Rated Pressure / Seat Test = 100% of Rated Pressure Testing per AWWA C517

ELASTOMER SELECTION CHART

SERVICE	ELASTOMER	AVERAGE USEFUL TEMP. RANGE	SERVICE	ELASTOMER	AVERAGE USEFUL TEMP. RANGE	SERVICE	ELASTOMER	AVERAGE USEFUL TEMP. RANGE
Acetone	EPDM	-35°F to 250°F	Caustic Soda	EPDM	-35°F to 250°F	Oil Animal	Nitrile	-20°F to 212°F
Air	EPDM	-35°F to 250°F	Cement Slurry	EPDM	-35°F to 250°F	Oil Mobil Therm Light	Viton	10°F to 250°F
Air w/Oil	Nitrile	0°F to 212°F	Copper Sulphate	EPDM	-35°F to 250°F	Oil Mobil Therm 600	Viton	10°F to 250°F
Alcohol, Amyl	EPDM	0°F to 212°F	Creosote (Coal)	Nitrile	-20°F to 212°F	Oil Mobil Therm 603	Nitrile	-20°F to 212°F
Alcohol, Aromatic	Viton	10°F to 250°F	Coal Slurry	Nitrile	-20°F to 212°F	Oil Lubricating	Nitrile	-20°F to 212°F
Alcohol, Butyl	Neoprene	-20°F to 225°F	Diesel Fuel No. 3	Nitrile	-20°F to 212°F	Oil Vegetable	Nitrile	-20°F to 212°F
Alcohol, Denatured	Nitrile	-20°F to 212°F	Diethylene Glycol	EPDM	-35°F to 250°F	Paint Latex	Nitrile	-20°F to 212°F
Alcohol, Ethyl	EPDM	-20°F to 250°F	Ethylene Glycol	EPDM	-35°F to 250°F	Phosphate Ester	EPDM	-35°F to 250°F
Alcohol, Grain	Nitrile	-20°F to 212°F	Fatty Acid	Nitrile	-20°F to 212°F	Propane	Nitrile	-20°F to 212°F
Alcohol, Isopropyl	Neoprene	-20°F to 225°F	Fuel Oil No. 2	Nitrile	-20°F to 212°F	Rape Seed Oil	EPDM	-35°F to 250°F
Alcohol, Methyl	EPDM	-20°F to 250°F	Fertilizer Liquid ($H_4N_2O_2$)	EPDM	-35°F to 250°F	Sewage with Oil	Nitrile	-20°F to 212°F
Ammonia, Anhydrous	Neoprene	-20°F to 225°F	Gasoline Keg	Nitrile	-20°F to 212°F	Sodium Hydroxide 20%	EPDM	-35°F to 250°F
Ammonia, Nitrate	EPDM	-20°F to 250°F	Gas Natural	Nitrile	-20°F to 212°F	Starch	EPDM	-35°F to 250°F
Ammonia, Water	EPDM	-20°F to 250°F	Glue Animal	Nitrile	-20°F to 212°F	Steam 250°F	EPDM	-35°F to 250°F
Animal Fats	Nitrile	-20°F to 212°F	Green Liquor	EPDM	-20°F to 212°F	Stoffard Solvent	Nitrile	-20°F to 80°F
Black Liquor	EPDM	-20°F to 250°F	Hydraulic oil	Nitrile	-20°F to 212°F	Sulphuric Acid 10% 50%	Neoprene	-20°F to 158°F
Blast Furnace Gas	Neoprene	-20°F to 225°F	Hydrogen	Nitrile	-20°F to 212°F	Viton	10°F to 300°F	
Butane	Nitrile	-20°F to 212°F	JP4 JP5	Viton	-20°F to 212°F	Sulphuric Acid 100%	Viton	10°F to 300°F
Bunker Oil "C"	Nitrile	-20°F to 212°F	Kerosene	Nitrile	0°F to 212°F	Trichlorethylene Dry	Viton	10°F to 300°F
Calcium Chloride	EPDM	-20°F to 250°F	Ketone	EPDM	-35°F to 250°F	Triethanol Amine	EPDM	-35°F to 250°F
Carbon Dioxide	EPDM	-20°F to 250°F	Lime Slurry	EPDM	-35°F to 250°F	Varnish	Viton	10°F to 300°F
Carbon Monoxide (Cold)	Neoprene	-20°F to 150°F	Methane	Nitrile	-20°F to 212°F	Water, Fresh	EPDM	-35°F to 250°F
Carbon Monoxide (Hot)	Viton	10°F to 300°F	Methyl Ethyl Ketone	EPDM	-35°F to 250°F	Water, Salt	EPDM	-35°F to 250°F
Carbon Tetrachloride	Viton	10°F to 300°F	Naptha (Berzin)	Nitrile	-20°F to 212°F	Xylene	Viton	10°F to 300°F

Note: Above elastomer / temperature chart are guidelines only.

ELASTOMERS AVAILABLE FOR MILLCENTRIC® PLUG VALVE

Natural rubber is also available.

NITRILE

A general purpose material sometimes referred to as BUNA-N or HYCAR with a -20°F to 212°F temperature range. Used on sewage, water, hydrocarbon and mineral oils.

EPDM

An excellent polymer for use on chilled water through to LP steam applications having a temperature range of -35°F to 250°F. Resistance to many acids, alkalies, detergents, phosphate esters, alcohols and glycols is an added benefit.

NEOPRENE

This versatile material shows outstanding resistance to abrasion and ozone. Chemical resistance to a wide range of petroleum base products and dilute acids and alkalies. Temperature range -20°F to 225°F.

VITON

Retention of mechanical properties at high temperature is an important feature of this elastomer: temperature range is -10°F to 300°F. It also has excellent resistance to oils, fuels, lubricants and most mineral acids and aromatic hydrocarbons.


Note: Not for water or steam applications.

1/2" - 2" MILLCENTRIC®

Eccentric Plug Valve

THREADED END:

FIG. 613A DUCTILE IRON / 603AS STAINLESS STEEL 1/2" - 2"




THREADED ENDS

SIZE	1/2	3/4	1	1-1/4	1-1/2	2
A	2.13	2.13	2.13	3.00	2.13	3.00
B	1.88	1.88	1.88	2.50	2.50	2.50
C	4.00	4.00	4.00	5.50	5.50	5.50
D	1/2" NPT	3/4" NPT	1" NPT	1-1/4" NPT	1-1/2" NPT	2" NPT
E	1.81	1.81	1.81	2.50	2.50	2.50
F	4.38	4.38	4.38	5.00	5.00	5.00
Weight (approx.)	7.50	7.25	7.00	13.00	11.75	10.00

FLANGED END:

FIG. 611A DUCTILE IRON / 601S STAINLESS STEEL 2"



FLANGED ENDS	
Size	2
Weight (approx.)	18.00

Note: Raised face is only on the 2" Fig. 601AS Stainless Steel.

NOTES

MILLIKEN®

Product Guide




FIGURE 600/601

Eccentric Plug Valve

Flanged and MJ

- Welded Nickel Seat
- Stainless Steel Bearings
- ANSI-B16.1 Flanges
- Solid Ductile Iron Plug
- Low Pressure Drop
- Flanged & MJ Ends
- Sizes 2" - 72" FL
- Sizes 3" - 48" MJ



FIGURE 601SS

Eccentric Plug Valve

Flanged and MJ

- Integral Stainless Seat
- Stainless Bearings
- Stainless Steel Body
- ANSI B16.5 Class 150 Flanges
- Solid Stainless Steel Plug
- Low Pressure Drop
- Size: 1/2" - 24"



FIGURE 601RL

Eccentric Plug Valve

Rubber Lined

- Soft or Hard Rubber Lining
- Stainless Steel Bearings
- ANSI B16.1 Flanges
- Solid Ductile Iron Plug
- Low Pressure Drop
- Sizes 3" - 54"
- Metal Plugs Available
- Consult Factory



FIGURE 602

Eccentric Plug Valve

High Pressure

- Ductile Iron Body
- ANSI B16.1 Flanges
- MJ AWWA C111
- Welded Nickel Seat
- Solid Ductile Iron Plug
- Low Pressure Drop
- Sizes 2" - 72" FL
- Sizes 3" - 48" MJ




FIGURE 613A

Eccentric Plug Valve

Threaded End

- Ductile Iron Construction
- Round Port
- Stainless Steel Bearings
- Low Pressure Drop
- Memory Stop
- NPT End Connections
- Sizes 1/2" - 2"




FIGURE 604E

Eccentric Plug Valve

Three Way Valve

- Epoxy Seat
- Solid Ductile Iron Plug
- Stainless Steel Bearings
- Low Pressure Drop
- Lift & Turn NOT Required
- High Solids & Flow Capacity
- Sizes 3" - 16"



FIGURE 606

Eccentric Plug Valve

Grooved End

- Welded Nickel Seat
- Stainless Steel Bearings
- AWWA C-606 Grooved
- Solid Ductile Iron Plug
- Low Pressure Drop
- Ductile or Steel Pipe
- Sizes 3" - 24"




FIGURE 611/610

Eccentric Plug Valve

Flanged and MJ

- Ductile Iron Body
- ANSI B16.1 Flanges
- MJ AWWA C111
- Welded Nickel Seat
- Solid Ductile Iron Plug
- Low Pressure Drop
- Sizes 2" - 72" FL
- Sizes 3" - 48" MJ



FIGURE 625

Eccentric Plug Valve

Flanged

- Available in Threaded and Flanged Ends
- Rated for 175 psi
- Sizes 1/2" - 4"
- UL / CGA Listed




FIGURE 600FP/601FP

Eccentric Plug Valve

Flanged and MJ

- Full / 100% PORT
- Welded Nickel Seat
- Stainless Steel Bearings
- ANSI-B16.1 Flanges
- Solid Ductile Iron Plug
- Low Pressure Drop
- Flanged & MJ Ends
- Sizes 2" - 48" FL
- Sizes 3" - 48" MJ




FIGURE 396/397

General Service Butterfly Valve

Flanged and MJ

- Meets MSS SP 67
- Ductile Iron Body
- DI-NP Disc
- Other Materials Upon Request
- Wrench or Gear Operated Available
- 2" - 48" Size Range



FIGURE 510A/511A

AWWA Butterfly Valve

Flanged and MJ

- Complies with AWWA C-504
- Class 150B Flanged or MJ
- Cast Iron Body and Disc
- Seat in Body
- Flow Through Disc on 24" and Larger
- Epoxy Paint on All Sizes Standard
- 3" - 72"



FIGURE 8500

AWWA Swing Check

Flanged

- Full Waterway
- Ductile Iron Construction
- Weight or Spring
- Air Cushion
- SS Body Seat Ring
- Buna Disc Insert
- Sizes 3" - 24"



FIGURE 8000

AWWA Swing Check

Flanged

- Full Waterway
- Weight or Spring
- Bronze / SS Body Seat Ring
- Bronze / Buna / EPDM Disc Insert
- Sizes 2" - 36"



FIGURE 9000

AWWA Swing Check

Flanged

- Clear Waterway
- Weight or Spring
- Air or Oil Cushion
- Bronze / SS Body Seat Ring
- Bronze / Buna / EPDM Disc Insert
- Sizes 3" - 72"



FIGURE 720A

Wafer Check Valve

Flanged

- Center Guided
- Check Valve
- Rated for 250 psi
- SS Disc / EPDM Seat
- Sizes 2" - 12"




FIGURE 700

Wafer Check Valve

Flanged

- ANSI Class 125 / 150
- High Flow Capacity
- Narrow Face-to-Face
- Sizes 3" - 12"
- 316 SS Internals
- Disc Position Indicator




FIGURE 851

Flex Check

Flanged

- Million Cycle Certification
- Complete Ductile Iron Construction
- 250 psi Pressure Rating
- Fully Epoxy Lined Interior
- No Internal Shafts, Bearings or Bushings
- No External Levers, Weights or Springs
- Mechanical Indicator (3" - 16")
- 2" - 24" Size Range
- Backflush Devices
- Proximity Switches



FIGURE 740A

Double Disc Check Valve

Flanged

- Wafer Pattern Check Valve Rated for 250 psi
- Available in Sizes 2" - 36" With a SS Disc / EPDM Seat



FIGURE 821A

Global Style Check Valve

Flanged

- Center Guided Check Valve
- SS Disc / EPDM Seat and is Available in Sizes 2" - 24"

For more information about us or to view our full line of water products, please visit www.millikenvalve.com or call Milliken customer service at 1.800.423.1323.

Mueller refers to one or more of Mueller Water Products, Inc., a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, Jones®, Mi.Net®, Milliken®, Pratt®, Pratt Industrial®, Singer®, and U.S. Pipe Valve & Hydrant. Please see www.muellerwp.com about to learn more.

Copyright © 2025 Henry Pratt Company, LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).